

DUAL 12 GOLD



One operator simultaneously supplies two transplanting rows.

Plant storage: tray holders not-supplied, choice of 4 sided revolving tray holders (single or double), 6 sided revolving tray holders or horizontal racks with 2 or more shelves.

Distribution system: horizontal with continuous rotation (without jerking), 12 cups with opening bottom and combined-row quincunx distribution.

Soil adaptation: independent and floating transplant units. High range parallelogram for a constant horizontality, reversible and adjustable spring in order to increase or reduce the weight on the packing wheels, front flex adjustable wheels and jointly liable with the cross-joint. New cross-joint with high sensitivity.

Automatic disengagement: in case of accidental stoppage with automatic and self-timing re-engagement.

Plant control: device for precise and constant planting.

Packing wheels: in flex rubber bi-convergent to triple regulation for an optimal earthing up.

Furrow opener ploughshare: quick release with anti-release system, anti-wear fusion on the bottom.

Wheel scraper: high efficiency with double adjustment (height and incidence).

Distance between rows:

- From 35 cm to 50 cm/14"-20" standard version - flex rubber wheels 410x80 mm.
- From 30 cm to 50 cm/12"-20" on request without extra cost - flex rubber wheels 410x60 mm.

Plant to plant spacing:

- Adjustable from 14 cm to 50 cm/6"-20" standard (from 31 cm to 82 cm/12"-32" optional).
- Adjustable from 14 cm to 50 cm/6"-20" with Rapid Shift (from 26 cm to 81 cm/10"-32" optional).

Transmission: mechanical with drive wheels and hexagonal bar (no PTO).

Indicative production: Up to 5000/7000 plants/hour per operator.



Unit	Unit	2 rows	4 rows	6 rows	8 rows	10 rows	12 rows
30 - 50 cm	35 - 50 cm	Standard frame 200 cm. 1 ^a cat.	Reinforced frame 250 cm. 2 ^a cat.	Reinforced frame 350 cm. 2 ^a cat.	Reinforced frame 400 cm. 2 ^a cat. extra	Reinforced frame 450 cm. 2 ^a cat. extra	Reinforced frame 600 cm. 3 ^a 4 ^a cat. extra
Without frame and without driving wheels							

DUAL 12 GOLD

Without trayholder

Cod. 500941	Cod. 510103	Cod. 80206202	Cod. 80206204	Cod. 80206206	Cod. 80206208	Cod. 80206210	Cod. 80206212
€ 3.896,00	€ 4.961,00	€ 9.223,00	€ 13.597,00	€ 17.958,00	€ 24.996,00	€ 29.959,00	

WITH FOLDING HYDRAULIC FRAME - TPI -

Without trayholder

Cod. 80206306	€ 17.557,00
---------------	-------------

WITH DOUBLE OPENING TELESCOPIC HYDRAULIC FRAME - TSIX -

Without trayholder

Cod. 80206416	€ 19.931,00
---------------	-------------

CLOD DIMENSIONS AND RELATED SHARES



OPTIONAL Cod. 500778	ON EQUIPMENT Cod. 500757	OPTIONAL Cod. 500756
-------------------------	-----------------------------	-------------------------

NARROW share

STANDARD share

LARGE share



A = 1,5 + 2,5

A = 2,0 + 3,0

A = 4,5 + 5,5

DUAL 12 GOLD

	2	4	6	6TPI	8	10	12
--	---	---	---	------	---	----	----

A cm - inches	210-83	210-83	210-83	210-83	210-83	210-83	210-83
B cm - inches	200-79	250-98	350-138	250/450-98/177	400-158	450-177	600-236
A₁ cm - inches	150-59	150-59	150-59	150-59	150-59	150-59	150-59
kg kg - lbs	440-970	740-1631	1010-2227	1800-3968	1425-3142	1840-4057	2200-4850
HP HP - kW	30-22	40-30	55-41	90-67	75-56	95-71	110-82