

Specifications

Service	Agricultural										Highway				
	MODEL	P-503	P-505	P-508/3S	P-509-60	P-510/3S	P-511-60	P-516	P-516G	P-516/3S	P-524	P-503H	P-50710/4EP	P-50711/4EP	P-5103S/4E
GROSS WEIGHT	1.5 tonnes	2.5 tonnes	4 tonnes	4 tonnes	5 tonnes	5 tonnes	8 tonnes	8 tonnes	8 tonnes	12 tonnes	1.5 tonnes	3.5 tonnes	3.5 tonnes	5 tonnes	
BOX (dimensions)	50"x72"x12G	5'x8'x3/16"	5'3"x8'3"x3/16"	6'x8'0"x3/16"	6'3"x8'3"x3/16"	6'x9'0"x3/16"	6'x9'0"x3/16"	5'x10'x3/16"	5'x10'x3/16"	7'5"x10'x3/16"	7'x12'x3/16"	6'0"x7'2"x12G	6'3"x8'3"x3/16"	6'x8'0"x3/16"	7'5"x10'0"x3/16"
SIDE PANEL	12" x 12G	14" x 12G	14" x 12G	14" x 12G	14" x 12G	14" x 12G	14" x 12G	16" x 12G	16" x 12G	16" x 12G	24" x 12G	12" x 12G	14" x 12G	14" x 12G	16" x 12G
FRONT/BACK PANEL (removable)	12"x14"x12G	19" x 12G	19" x 12G	19" x 12G	19" x 12G	19" x 12G	19" x 12G	24" x 12G	24" x 12G	24" x 12G	32"x 12G	12"x14" x12G	19" x 12G	19" x 12G	24" x 12G
PLATFORM HEIGHT	22"	34"	33"	33"	33"	33"	32"	32"	35"	39"	22"	34"	33"	35"	
OVERALL LENGTH	7'6"	12'0"	11'6"	12'3"	11'6"	12'3"	14'6"	14'6"	14'0"	16'6"	7'6"	11'6"	12'3"	14'0"	
OVERALL WIDTH	4'5"	5'4"	5'8"	5'10"	5'8"	5'10"	7'5"	7'5"	7'11"	7'6"	4'5"	5'8"	5'10"	7'11"	
OVERALL HEIGHT	36"	55 1/2"	60"	60"	60"	60"	62"	62"	65"	72"	36"	60"	60"	65"	
FREE HEIGHT/MAX. LIFT	10"	15"	20"	14"	20"	20"	15"	15"	20"	20"	10"	20"	20"	20"	
THREAD WIDTH	36 1/4"	44 1/2"	51"	60"	51"	60"	74"	74"	75"	72 1/2"	36 1/4"	52 1/2"	61 1/2"	78"	
DUMPING ANGLE (back)	47 deg.	47 deg.	47 deg.	47 deg.	47 deg.	47 deg.	47 deg.	47 deg.	47 deg.	47 deg.	47 deg.	47 deg.	47 deg.	47 deg.	
DUMPING ANGLE (2 sides)	47 deg.	..	47 deg.	47 deg.	47 deg.	..	47 deg.	
GRAIN DOOR	Std.	..	Std.	
AXLE	Tandem	Tandem	Single	Single	Tandem	Tandem	Tandem	Tandem	Tandem	Tandem	Tandem	Tandem	Tandem	Tandem	Tandem
SUSPENSION	Springs	Springs	Springs	
HUBS	4 bolts	5 bolts	6 bolts	6 bolts	6 bolts	6 bolts	6 bolts	6 bolts	6 bolts	6 bolts	8 bolts	4 bolts	
HUB CAPACITY	1000 lbs	2500 lbs	5000 lbs	5000 lbs	4000 lbs	4000 lbs	5000 lbs	5000 lbs	5000 lbs	5000 lbs	5500 lbs	1000 lbs	
SPINDLES	1 1/4"	1 3/4"	2"	2"	1 3/4"	1 3/4"	2"	2"	2"	2"	2 1/4"	
WHEELS	4	4	2	2	4	4	4	4	4	4	4	4	4	4	
WHEEL DIMENSION	8.5" x 8"	12" x 8.5"	15" x 8"	15" x 8"	15" x 6"	15" x 6"	15" x 8"	15" x 8"	15" x 8"	15" x 8"	15" x 10"	8.5" x 8"	14" x 6"	14" x 6"	15" x 6"
TIRES (standard)	18 x 8.5 x 8"	23"x10.5"x12"	11L15 8p	11L15 8p	9.5L15 6p	11L15 6p	11L15 8p	11L15 8p	11L15 8p	11L15 8p	12.5L15 10p	18.5x8.5x8	ST205/75R14	ST205/75R14	ST225/75R15
HITCH: CLEVIS/SWIVEL	standard	standard	standard	standard	standard	standard	standard	standard	standard	standard	standard	option	option	option	option
HITCH: BALL COUPLER	std. 2"	std. 2 5/16"	std. 2 5/16"	std. 2 5/16"
ELECTRIC BRAKES	standard	standard	standard
LIGHT SYSTEM (12 V)	standard	standard	standard	standard
OIL VOLUME REQUIRED	5 L	..	5 L	5.2 L	11 L	..	5 L	..	5.2 L
CYLINDER	1 double ac	1 double ac	1 single ac	1 double ac	1 single ac	1 double ac	2 double ac	2 double ac	1 single ac	1 single ac	1 double ac	1 double ac	1 single ac	1 double ac	1 single ac
BRAKE AWAY KIT	standard	standard	standard
BATTERY (12V)	standard	standard	standard
SAFETY CHAINS	standard	standard	standard
TOTAL WEIGHT	565 lbs	1550 lbs	1775 lbs	1885 lbs	1850 lbs	1960 lbs	1980 lbs	1980 lbs	1980 lbs	1980 lbs	3400 lbs	565 lbs	1850 lbs	1925 lbs	3180 lbs

*Turf Saver (4 ply)

Design and specifications subject to change without notice

Revised 6-1-04 (Based on Mfg. Price List 1-1-04)

Prices subject to change without notice



Code AT-3